

## Alba BT

Manufacturing process	Tufted	ISO 2424
Gauge	5/32" Cutpile	
Pile yarn composition	100% PA6	ISO 2424
Primary backing	Non Woven	
Backing	BT	
Width	50*50 cm, 100*25 cm	
Pile weight	830 g/m <sup>2</sup>	
Total weight	3910 g/m <sup>2</sup>	+/- 15% ISO 8543
Pile height	5,5 mm	ISO 1765
Total height	8.2 mm	+15% / -10% ISO 1765
Number of tufts	118440	
Overall use class	Commercial 32, Areas with medium use	EN 1307
Luxury class	LC2	EN 1307
Castor chair suitability	Yes, permanent use	EN 985
Stair suitability	No	EN 1307
Colour fastness to light	≥ 5	ISO 105-B02
Colour fastness to rubbing, wet and dry	≥ 4	ISO 105-X12
Colour fastness to water	≥ 4	ISO 105-E01
Colour fastness to soiling	≥ 3,5	EN 1269
Electrostatic charging	< 2kV	ISO 6356
Vertical resistance	< 1,0x10 <sup>8</sup> Ω	ISO 10965
Horizontal resistance	< 1,0x10 <sup>8</sup> Ω	ISO 10965
Thermal resistance	0.1 m <sup>2</sup> .K/W	ISO 8302
Slip resistance	> 0,3 Machine direction > 0,3 Crossdirection	EN 13893
Flammability	Bfl,s1	EN 13501-1
Prodis-ID (GuT)	B2E3BC2C	www.pro-dis.info

## Floorsymbols



## Certificates

