ERGOMAT Bubble-Down XL

The Ergomat Bubble-Down XL is made of pure polyurethane and is designed to increase comfort while reducing tripping hazards, body aches, quality issues, and sick leaves. This is the ultimate mat for dry environments or where there is an extreme amount of pivoting.

Unmatched Safety Features

- Gradually sloping 3.5” (9cm) yellow bevel
- Any size, any shape mat, always in one piece
  - No overlapping or worn-out connecting mats, also eliminating tripping hazards
- 1” (2.5cm) thick mat

Highest Quality

- Raw virgin material only
  - Unbeaten durability and ergonomic relief
- Not only anti-fatigue, but the first true ergonomic smooth mat
  - Unique ergonomic design, eliminating and preventing common problems encountered in standing environments, by stimulating the body to increase blood circulation and alertness, reducing sick leaves, worker’s compensation and quality issues.

The Bubble-Down Advantage

- Solid mat throughout, no hollow bubbles that collapse
  - Long-term solution to keep the “bounce back” effect throughout the warranty period
- Anti-static properties
- Silicone & latex-free

5-Year Warranty

All Ergomat product lines are conditionally warranted against normal usage* 24 hours a day, 7 days a week. The warranty does not cover damage caused by the mat being dragged or pulled from a heavy load or items being pushed or dragged across the product, such as skids or pallets. The warranty against chemicals, oils, liquids, or other matter differs with the type of mat. Please consult your dealer or an Ergomat Rep to select the correct mat for your environment. The warranty periods starts from the date of purchase. The warranty only covers the replacement of the product, no direct or indirect costs are covered.
* It is considered normal usage when a person stands or walks on the Ergomat with regular footwear in an environment where the temperature is under 25° C (77° F) and the humidity is below 80%.

This mat requires add-on bevels. It can also be supplied with holes for drainage and air flow.

ERGOMAT®

www.ergomat.com - info@ergomat.com
US: +1-440-282-4651
English (EU): +44 03308 280 084
Scandanavia: +45 70 22 18 40
German: +49 9524 30367-50
French: +33 1 446 410 28
Dutch: +31 73 613 05 30

Properties	Standard	ERGOMAT Bubble-Down XL
Material		Foamed Polyurethane
Color		Anthracite
Weight		3900 g +/- 50 g // 8.6 lbs +/- 0.1 lbs
Length without beveled edges		89 cm +/- 1% // 35" +/- 0.38"
Width without beveled edges		59 cm +/- 1% // 23.25" +/- 0.38"
Thickness		25 mm // 1"
Density	ISO 2781	380 kg/m³ +/- 10 %
Hardness	DIN 53505	22-30 Sh A
Compression Pressure face = ø 100mm % by pressure of 240kg	Ergomat A/S Standard	50%
Abrasion Load = 5 N	ISO 46 49 (5 N)	180 mm³ // 7 in³
Breaking Point / tensile strength	EN ISO 527-1	2 Mpa
Elongation at break	EN ISO 527-1	500%
Tearing strength	ASTM D 624	4 N/mm
Electrical Resistance Surface point to point % 50 RH	ESD STM7	1 x 10^9 Ω - 5 x 10^9 Ω
Fire behavior		Not Tested
Thermal properties Minimum use Maximum use Maximum short duration	The ergonomic properties remain	0°C // 32°F 25°C // 77°F 40°C // 115°F
UV-resistance		Inferior
Hydrolytic resistance		Inferior
Warranty		5 years